

In the claims:

Kindly amend the claims to read as follows:

1. (Currently amended) A device (1) for treating compressed air, intended to be installed in an industrial vehicle[[,]] comprising a motor vehicle able to haul a trailer, including:
 - an air inlet (3) for air coming from a compressed-air source (7);
 - at least one air outlet (4) connected to a reservoir or reservoirs ~~intended~~ to supply ~~the a~~ service brake system;
 - a set of electropneumatic components (37) distributing compressed air from the compressed-air source bound for the reservoir or reservoirs;
 - an electronic command and control unit (10), able to operate said set of electropneumatic components (37), the command and control unit being connected to a computer communication bus (30) and to various electrical components ~~such as sensors or contact switches, ;~~~~characterized in that it also comprises:~~
 - a at least one supplementary air outlet (26) ~~intended~~ to supply an ~~the~~ actuator or actuators of ~~the a~~ pneumatic suspension system of one axle;
 - a supplementary set of electropneumatic components (27) which are associated with the supplementary air outlet (26); and
 - operating means incorporated into the electronic command and control unit (10), ~~able~~ to operate the supplementary set of electropneumatic components (27) on the basis of information originating from the computer communication bus (30) and/or from various electrical components.
2. (Currently amended) The device as claimed in claim 1, wherein ~~characterized in that~~ the supplementary air outlet and the set of associated electropneumatic components, are arranged in an element (16) attached to a ~~the~~ body (2) of the device.

3. (Currently amended) The device as claimed in claim 1, wherein supplementary ~~characterized in that the~~ air outlets ~~intended~~ for supplying the pneumatic suspension system which are attached to an axle are grouped together into one and the same element attached by flanges to ~~a the~~ body of the device.
4. (Currently amended) The device as claimed in claim 1, wherein ~~characterized in that~~ the electronic command and control unit ~~(10)~~ is interfaced with one or several altitude sensors ~~(34)~~ measuring ~~the a~~ difference in height between the chassis of the vehicle and one or several points of the axle ~~concerned~~.
5. (Currently amended) The device as claimed in claim 1, further comprising ~~characterized in that it also comprises:~~
 - at least one additional supplementary air outlet ~~intended~~ or outlets to supply an the actuator or actuators of a the motor vehicle parking brake system of the motor vehicle;
 - an additional set of electropneumatic components ~~members~~, which is associated with the additional supplementary air outlet or outlets;
 - operating means incorporated into the electronic command and control unit ~~and~~ able to operate the additional set of electropneumatic components ~~members~~ on the basis of information originating from the computer communication bus and/or various electrical components.
6. (Currently amended) The device as claimed in claim 5, wherein ~~characterized in that~~ the additional supplementary air outlet or outlets ~~intended~~ to supply the motor vehicle parking brake system, and the additional set of associated electropneumatic components ~~members~~, are gathered together into an element ~~(13-16)~~ attached to a the body of the device.

7. (Currently amended) The device as claimed in claim 1, further comprising
~~characterized in that it also comprises:~~
 - at least one complementary air outlet ~~intended~~ or outlets to supply ~~a the~~ pneumatic actuator or actuators of an auxiliary system ~~such as, in particular, a differential lock system, a movement take-off system,~~
 - a complementary set of electropneumatic components ~~members~~ which is associated with the complementary air outlet or air outlets,
 - operating means incorporated into the electronic command and control unit able to operate the complementary set of electropneumatic components ~~members~~ on the basis of information originating in particular from the computer communication bus.
8. (Currently amended) The device as claimed in claim 1, further comprising
~~characterized in that it also comprises~~ means for dehumidifying ~~the~~ air originating from the compressed-air source.
9. (Currently amended) The device as claimed in claim 8, wherein ~~characterized in that~~ the means for dehumidifying the air comprises a cartridge (5) that can be removed from a the body (2) of the device.
10. (Currently amended) The device as claimed in claim 2, further comprising
~~characterized in that it also comprises~~ one or several supplementary elements (17, 18) attached to the body (2) of the device, each element having one or several electrical contacts able to be incorporated into an electric control circuit, said contacts being operated by the command and control unit (10) on the basis of information from the computer communication bus and/or various electrical components.
11. (New) The device as claimed in claim 7, wherein the auxiliary system comprises at least one of a differential lock system and a movement take-off system.